

Signature	Revision History	Date	Rev.
Norman Xu	For Bulk Production	Dec.20,2005	01

1	2	3	4	5	6	7																		
<p>A USB A TYPE MALE PLASTIC:WHITE</p> <p>B USB B TYPE MALE PLASTIC:WHITE</p> <p>2000±30mm</p> <p>NOTE:4</p>						A																		
<p>NOTES:</p> <p>1. CABLE:UL-2725 [28AWG(7/0.127)*1PR+24AWG(7/0.203)*2C +AL-FOIL/MYLAR+DRAIN WIRE(7/0.127)+65% BRAID]TIN PVC JACKET OD:4.7±0.15mm COLOR:BEIGE, REV 2.0</p> <p>2.CONNECTER: P1:USB A TYPE MALE GOLD PLATED 30u" CONTACT, NICKEL PLATED SHELL REV 2.0. P2:USB B TYPE MALE GOLD PLATED 30u" CONTACT, NICKEL PLATED SHELL REV 2.0. 3.HOOD: MOLDED TYPE,PVC 45P, COLOR:BEIGE. 4.TOOLING CAVITY INDICATION FOR INSPECTION 5.ELECTRICLE TEST: <1>100% OPEN SHORT & MIS WIRE TEST. <2>CONTACT RESISTANCE 3 Ohms MAX. <3>INSULATION RESISTANCE 20M Ohms MIN. 6.PACKING:SEE P-0039 REV.C PACKING DRAWING PACKING TYPE: DB VP3 (HANKING SIZE MUST BE SMALLER THAN PACKING)</p>						D																		
<p>E</p> <table border="1"> <tr> <td>P1</td> <td>RED 1</td> <td>VCC</td> </tr> <tr> <td></td> <td>WHITE 2</td> <td>-DATA</td> </tr> <tr> <td></td> <td>GREEN 3</td> <td>+DATA</td> </tr> <tr> <td></td> <td>BLACK 4</td> <td>GROUND</td> </tr> <tr> <td></td> <td>SHELL</td> <td>BRAID</td> </tr> <tr> <td></td> <td></td> <td>SHELL</td> </tr> </table>						P1	RED 1	VCC		WHITE 2	-DATA		GREEN 3	+DATA		BLACK 4	GROUND		SHELL	BRAID			SHELL	E
P1	RED 1	VCC																						
	WHITE 2	-DATA																						
	GREEN 3	+DATA																						
	BLACK 4	GROUND																						
	SHELL	BRAID																						
		SHELL																						
<p>F</p>						F																		
<p>G</p>						G																		
<p>H</p> <p>RoHS Compliant</p> <p>EAN Code: 4016032117797</p>						H																		

Drawn by	Dec.20,2005	Norman Xu
Checked by	Dec.20,2005	Alex Dan
Approved by		

Part No.	AK 672/2
Title:	USB 2.0 Cable, 2.0M

ASSMANN
Electronic GmbH

Scale	N/A	Sheet	1/1
Unit	MM		

STR1407